

1. Identification

Product identifier Foaming Instant Hand Sanitizer
Other means of identification
 SDS number 16SAM03084A
 Product code HIL00410
Recommended use Instant Hand Sanitizer
Recommended restrictions For Labeled Use Only

This is a personal care or cosmetic product that is safe for consumers and other users under normal and reasonably foreseeable use. Cosmetics and consumer products, specifically defined by regulations around the world, are exempt from the requirement of an SDS for the consumer.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer
Company name HILLYARD INDUSTRIES
Address 302 North Fourth St.
 St. Joseph, MO 64501

Contact person Regulatory Affairs
Telephone number (816) 233-1321 (Ext. 8285)
Fax (816) 383-8485
E-mail regulatoryaffairs@hillyard.com
Emergency telephone # (800) 424-9300
 (Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident involving chemicals)

2. Hazard(s) identification

Physical hazards Flammable liquids Category 2
Health hazards Serious eye damage/eye irritation Category 2A
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements



Signal word Danger
Hazard statement Highly flammable liquid and vapor. Causes serious eye irritation.
Precautionary statement
 Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.
 Response If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.
 Storage Store in a well-ventilated place. Keep cool.

Disposal	Buyer assumes all risk and liability associated with disposal of this product (original concentration or dilution) in violation of applicable law in compliance with applicable federal, state and local requirements.
Hazard(s) not otherwise classified (HNOC)	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Ethanol		64-17-5	60 - < 70
Glycerine USP 99.7%		56-81-5	1 - < 3
Other components below reportable levels			30 - < 40

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists. If skin irritation or rash occurs, discontinue use.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Irritation of nose and throat. Coughing.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
----------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Use appropriate containment to avoid environmental contamination. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage**Precautions for safe handling**

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Ethanol (CAS 64-17-5)	PEL	1900 mg/m ³	
		1000 ppm	
Glycerine USP 99.7% (CAS 56-81-5)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.

US. ACGIH Threshold Limit Values

Components	Type	Value
Ethanol (CAS 64-17-5)	STEL	1000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Ethanol (CAS 64-17-5)	TWA	1900 mg/m ³
		1000 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes.

Skin protection	
Hand protection	Not applicable.
Other	Not applicable.
Respiratory protection	Not applicable.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Keep away from food and drink.

9. Physical and chemical properties

Appearance	Clear, colorless to slightly amber liquid
Physical state	Liquid.
Form	Liquid.
Color	Colorless to light amber
Odor	Floral / Alcohol odor
Odor threshold	Not available
pH	6.5 - 7.5
Melting point/freezing point	Not available
Initial boiling point and boiling range	178 °F (81.11 °C)
Flash point	73.0 °F (22.8 °C) Tag Closed Cup
Evaporation rate	< 1 Ethyl ether = 1
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	30.84 mm Hg
Vapor density	1.3222 AIR=1
Relative density	0.881 - 0.891 at 77°F
Solubility(ies)	
Solubility (water)	100 % complete
Partition coefficient (n-octanol/water)	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Other information	
Density	7.34 - 7.42 lb/gal
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Percent volatile	96 - 98 %
VOC	Not available

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Irritation of nose and throat. Coughing.

Information on toxicological effects

Acute toxicity Not known.

Product	Species	Test Results
----------------	----------------	---------------------

Foaming Instant Hand Sanitizer

Acute

Inhalation

LC50	Mouse	63 mg/l, 4 Hours
------	-------	------------------

Oral

LD50	Rat	10 g/kg
------	-----	---------

Components	Species	Test Results
-------------------	----------------	---------------------

Ethanol (CAS 64-17-5)

Acute

Inhalation

LC50	Mouse	39 mg/l, 4 Hours
------	-------	------------------

Oral

LD50	Rat	6.2 g/kg
------	-----	----------

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Prolonged inhalation may be harmful.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product	Species		Test Results
Foaming Instant Hand Sanitizer			
Aquatic			
Crustacea	EC50	Daphnia	10784.0215 mg/l, 48 hours estimated
Fish	LC50	Fish	16004.3594 mg/l, 96 hours estimated
Components	Species		Test Results
Ethanol (CAS 64-17-5)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	7.7 - 11.2 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/l, 96 hours
Glycerine USP 99.7% (CAS 56-81-5)			
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	51000 - 57000 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Ethanol	-0.31
Glycerine USP 99.7%	-1.76

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not contaminate ponds, waterways or ditches with chemical or used container. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations. Buyer assumes all risk and liability associated with disposal of this product (original concentration or dilution) in violation of applicable law.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F
The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1170
UN proper shipping name	ETHANOL SOLUTIONS (Ethanol) (Denatured Alcohol 40B, 190 Proof)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	24, IB2, T4, TP1
Packaging exceptions	150
Packaging non bulk	202
Packaging bulk	242
ERG number	127

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established.

DOT



General information

PACKAGES 1 LITER AND SMALLER ARE SHIPPED LIMITED QUANTITY

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List or Exempt.

This product is regulated by the FDA as an Over the Counter Drug Product. It is labeled in accordance with FDA regulations.

Toxic Substances Control Act (TSCA)

One or more components of the mixture are not on the TSCA 8(b) inventory or are designated "inactive".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

Yes

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)
Serious eye damage or eye irritation

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Ethanol (CAS 64-17-5)

Low priority

Glycerine USP 99.7% (CAS 56-81-5)

Other Flavoring Substances with OSHA PEL's

US state regulations

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	04-10-2015
Revision date	02-19-2020
Version #	04
HMIS® ratings	Health: 2 Flammability: 3 Physical hazard: 0

Disclaimer No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or disposal of these products.

Revision information This document has undergone significant changes and should be reviewed in its entirety.